

# Stuffing-Box-Packing Type 2017

## Description

Diagonally braided from gPTFE-yarn (PTFE with incorporated graphite), reinforced at the corners with continuous Aramid yarn, lubricated with silicone oil.

## Properties

**Style 2017** is a high performance multi-yarn packing, which combines the advantages of the supple gPTFE material with those of tough and durable Aramid. This results in reduced shaft-wear and better thermal conductivity than standard Aramid packings.

## Application areas

Multi-purpose packing, particularly well suited for use in piston-pumps, mixers, stirrers, reactors, for industrial and chemical process valves, good for high pressure applications.

## Application media

Can be used with a wide variety of media including abrasive ones: cold and hot water, steam, solvents, oils, greases, diluted acids and lyes, brine, sewage etc.

## Not suitable for

Highly concentrated acids and lyes, alkali metals, fluorine and fluorine compounds at high temperatures.

## Benefits

**TEADIT style 2017** is particularly well suited for difficult sealing applications, i.e. with high pressures or abrasive media, such ensuring longer service life. Combines exceptional extrusion resistance and high mechanical strength with good chemical and thermal stability.



### Temperature:

	- temp	+ temp
(°C)	100	280

### Pressure:

	rotating:	reciprocating:	static:
(bar)	30	200	200

pH: 2-12    density: (g/cm<sup>3</sup>) 1,6    v: (m/s) 20